



Best Selling

CLX ENet/IP 100M

Catalog #: 1756-EN2T
Lifecycle status: Active



Print page

ADD TO BOM

- Register Product
- Add to Repair Quote
- Get Support

Technical Specifications

Environmental

Drawings	Surrounding air temperature, max	60 °C
Documents	Storage temperature	-40 °C <Ta <85 °C (-40 °F <Ta <185 °F)
Certifications	Emissions	CISPR 11: Class A
Alternative Products	Vibration	2 G @ 10...500 Hz
Technotes	ESD immunity	6 kV contact discharges, 8 kV air discharges
	EFT/B immunity	±3kV @ 5kHz on Ethernet ports
	Relative humidity	5...95% noncondensing
	Shock	Operating: 30 G, Nonoperating: 30 G
	Conducted RF immunity	10V rms with 1 kHz sine-wave 80% AM from 150 kHz...80 MHz
	Surge transient immunity	±2 kV line-earth (CM) on Ethernet ports
	Operating temperature	0 °C <Ta <60 °C (32 °F <Ta <140 °F)
	Radiated RF immunity	10V/m with 1 kHz sine-wave 80% AM from 80...2000 MHz, 10V/m with 200 Hz 50% Pulse 100% AM @ 900 MHz, 10V/m with 200 Hz 50% Pulse 100% AM @ 1890 MHz, 3V/m with 1 kHz sine-wave 80% AM from 2000...6000 MHz

Contact your distributor in New Territories
[Change location](#)

Nam Wah Electrical Equipment HK Co. 

ROCKSTAR AUTOMATION TECHNOLOGY (HK) CO., 

[Find a partner >](#)



Copyright ©2025 Rockwell Automation, Inc.

