


# 3300 XL 11 mm Proximity Transducer System

## Datasheet

Bently Nevada Machinery Condition Monitoring

146256 Rev. P



## Description

### Transducer System

The 3300 XL 11 mm Proximity Transducer System consists of:

- 3300 XL 11 mm probe
- 3300 XL 11 mm extension cable
- 3300 XL 11 mm Proximitor Sensor<sup>1</sup>

The 3300 XL 11 mm Proximity Transducer System has a 3.94 V/mm (100 mV/mil) output for non-contacting vibration and displacement measurements on fluid film bearing machines. The large 11 mm tip enables this transducer system to have a longer linear range compared to our standard 3300 XL 8 mm Transducer System. It is primarily used in the following applications where the longer linear range is necessary:

- Axial (thrust) position measurements
- Ramp differential expansion measurements on steam turbines
- Rod position or rod drop measurements on reciprocating compressors
- Tachometer and zero speed measurements
- Phase reference (Keyphasor) signals

The 3300 XL 11 mm Proximitor Sensor is designed to replace the 7200-series 11 mm and 14 mm Transducer Systems. When upgrading from the 7200-series system to the 3300 XL 11 mm system, every component must be replaced with 3300 XL 11 mm components. In addition, the monitoring system must be updated. If using a 3500 Monitoring System, an updated version of the configuration software that lists the 3300 XL 11 mm Transducer System as a compatible option is required. Existing 3300 Monitoring Systems may need a modification.



Contact your local sales and service representative for assistance.



The 3300 XL 11 mm Proximity Transducer is designed for measuring position or vibration within a frequency range of 0 to 8 kHz. Typical applications of this system include radial vibration and position, axial position and Keyphasor measurements.

Although the terminals and connector on the Proximitor sensor have protection against electrostatic discharge, take reasonable precautions to avoid electrostatic discharge during handling.

## Proximitor Sensor

The 3300 XL 11 mm Proximitor Sensor has the same advanced features found in the 3300 XL 8 mm Proximitor Sensor. Its thin design allows it to be mounted in either a high-density DIN-rail installation or a more traditional panel mount configuration. Improved RFI/EMI immunity allows the 3300 XL Proximitor Sensor to achieve European CE mark approvals without any special mounting considerations. This RFI immunity also prevents the transducer system from being adversely affected by nearby high frequency radio signals. SpringLoc terminal strips on the Proximitor Sensor require no special installation tools and facilitate faster, highly robust field wiring connections.

## Proximity Probe and Extension Cable

The 3300 XL 11 mm probe comes in varying probe case configurations, including armored and unarmored  $\frac{1}{2}$ -20,  $\frac{5}{8}$ -18, M14 X 1.5 and M16 X 1.5 probe threads. The reverse mount 3300 XL 11 mm probe comes standard with either  $\frac{3}{8}$ -24 or M10 X 1 threads. All components of the transducer system have gold-plated brass ClickLoc connectors. ClickLoc connectors lock into place, preventing the connection from becoming loose. The patented TipLoc molding method provides a robust bond between the probe tip and the probe body. The probe cable is securely attached to the probe tip utilizing

our patented CableLoc design that provides 330 N (75 lb) pull strength.

3300 XL Probes and Extension Cables can also be ordered with a FluidLoc cable option. This option prevents oil and other liquids from leaking out of the machine through the cable's interior. The connector protector option provides additional protection of the connectors in a humid or moist environment. Connector protectors are recommended for all installations and provide increased environmental protection<sup>2</sup>. Additionally, the 3300 XL 11 mm probe comes standard with a locknut with pre-drilled safety wire holes.

Notes:

1. Proximitor Sensors are supplied by default from the factory calibrated to AISI 4140 steel. Calibration to other target materials is available upon request.
2. Silicone tape is also provided with each 3300 XL extension cable and can be used instead of connector protectors. Silicone tape is not recommended in applications where the probe-to-extension cable connection will be exposed to turbine oil.

## Specifications

Unless otherwise noted, the following specifications are for a 3300 XL 11 mm Proximitor Sensor, extension cable and probe between 0°C and +45°C (+32°F to +113°F) at a maximum altitude of 2000m, with a -24 Vdc power supply, a 10 k $\Omega$  load, our supplied AISI 4140 steel target that is 31 mm (1.2 in) diameter or larger, and a probe gap of 2.5 mm (100 mils). The system accuracy and interchangeability specifications do not apply when using a transducer system calibrated to any target other than our AISI 4140 steel target.

## Electrical

### Proximitor Sensor

|                    |  |
|--------------------|--|
| Input              | Accepts one non-contacting 3300 XL 11 mm Proximity Probe and Extension Cable.  |
| Power              | Requires -17.5 Vdc to -26 Vdc without barriers at 12 mA maximum consumption, -23 Vdc to -26 Vdc with barriers. Operation at a more positive voltage than -23.5 Vdc can result in reduced linear range. |
| Supply Sensitivity | Less than 2 mV change in output voltage per volt change in input voltage.  |
| Output resistance  | 50 $\Omega$  |

### Probe dc Resistance

| Probe Length (m) | Resistance from the Center Conductor to the Outer Conductor ( $R_{\text{PROBE}}$ ) (ohms) |
|------------------|---|
| 1.0              | 5.9 $\pm$ 0.5   |
| 5.0              | 7.2 $\pm$ 0.8   |
| 9.0              | 8.5 $\pm$ 1.1   |

### Extension Cable dc Resistance

| Length of Extension Cable (m) | Resistance from Center Conductor to Center Conductor ( $R_{\text{CORE}}$ ) (ohms) | Resistance from Coaxial Conductor to Coaxial Conductor ( $R_{\text{JACKET}}$ ) (ohms) |
|-------------------------------|---|---|
| 4.0                           | 1.0 $\pm$ 0.25  | 0.3 $\pm$ 0.1   |
| 8.0                           | 2.0 $\pm$ 0.5   | 0.6 $\pm$ 0.2   |

|                             |   |
|-----------------------------|---|
| Extension cable capacitance | 69.9 pF/m (21.3 pF/ft) typical  |
| Field wiring                | 0.2 to 1.5 mm <sup>2</sup> (16 to 24 AWG) [0.25 to 0.75 mm <sup>2</sup> (18 to 23 AWG) with ferrules]. Recommend using three-conductor shielded triad cable. Maximum length of 305 meters (1,000 feet) between the 3300 XL Proximitor Sensor and the monitor. See the frequency response graph for signal rolloff at high frequencies when using longer field wiring lengths. |
| Linear Range                | 4.0 mm (160 mils). Linear range begins at approximately 0.5 mm (20 mils) from target and is from 0.5 to 4.5 mm (20 to 180 mils) (approximately -1 to -17 Vdc). Extended Deviation from Straight Line (DSL) range is from approximately 0.5 to 5.0 mm (20 to 200 mils) (-1 to -19 Vdc). The extended DSL range is not applicable when using zener barriers.                    |
| Recommended Gap Setting     | 2.5 mm (100 mils)   |

|  |  |
|--|--|
| Incremental Scale Factor (ISF)                     | 3.94 V/mm (100 mV/mil) $\pm 10\%$ including interchangeability error when measured in increments of 0.5 mm (20 mils) over the 4.0 mm (160 mil) linear range.   |
| <b>Deviation from best fit straight line (DSL)</b> |  |
| Standard DSL range                                 | Less than $\pm 0.10$ mm ( $\pm 4$ mils).   |
| Extended DSL range                                 | Less than $\pm 0.15$ mm ( $\pm 6$ mils).   |
| System Performance over extended temperatures      | <p>Over a probe temperature range of <math>-35^{\circ}\text{C}</math> to <math>+120^{\circ}\text{C}</math> (<math>-31^{\circ}\text{F}</math> to <math>+248^{\circ}\text{F}</math>) with the Proximitor Sensor and extension cable between <math>0^{\circ}\text{C}</math> to <math>+45^{\circ}\text{C}</math> (<math>+32^{\circ}\text{F}</math> to <math>+113^{\circ}\text{F}</math>), the ISF remains within <math>\pm 25\%</math> of 3.94 V/mm (100 mV/mil), the DSL remains within <math>\pm 0.51</math> mm (<math>\pm 20</math> mils) and the extended range DSL remains within <math>\pm 0.59</math> mm (<math>\pm 23</math> mils)</p> <p>Over a Proximitor Sensor and extension cable temperature range of <math>-35^{\circ}\text{C}</math> to <math>+65^{\circ}\text{C}</math> (<math>-31^{\circ}\text{F}</math> to <math>+149^{\circ}\text{F}</math>) with the probe between <math>0^{\circ}\text{C}</math> to <math>+45^{\circ}\text{C}</math> (<math>+32^{\circ}\text{F}</math> to <math>+113^{\circ}\text{F}</math>), the ISF remains within <math>\pm 25\%</math> of 3.94 V/mm (100 mV/mil), the DSL remains within <math>\pm 0.51</math> mm (<math>\pm 20</math> mils) and the extended range DSL remains within <math>\pm 0.59</math> mm (<math>\pm 23</math> mils)</p> |
| Frequency Response                                 | 0 to 8 kHz: $+0$ , $-3$ dB typical, with up to 305 meters (1000 feet) of field wiring.   |

| <b>Cross-talk Limitation:</b>     |                  |
|-----------------------------------|------------------|
| <b>Target Size – Flat Surface</b> |                  |
| <b>Diameter</b>                   |                  |
| Recommended Minimum               | 30.5 mm (1.2 in) |
| <b>Shaft Diameter</b>             |                  |
| Recommended Minimum               | 152 mm (6.0 in)  |



When operating below recommended limits, there will be cross-talk between the probes. To minimize this effect, close the gap as much as possible while still keeping the needed linear range.

A shaft diameter of 76.2 mm (3.0 in) can keep the cross-talk below 50 mV by having the minimum separation of transducer tips; it needs to be at least 64 mm (2.5 in) for axial position measurements and 58 mm (2.3 in) for radial vibration measurements.

Many factors affect the cross-talk when operating below the recommended limit. Consult Performance Specification, document 144979 for additional information.

| <b>Effects of 60 Hz Magnetic Fields Up to 300 Gauss (5 meter system)</b> |                   |       |            |
|--|-------------------|-------|------------|
| <b>Output voltage in mil pp/gauss</b>                                    |                   |       |            |
| Gap  | Proximitor Sensor | Probe | Ext. Cable |
| 0.5 mm (20 mil)  | 0.006             | 0.001 | 0.001      |
| 2.5 mm (100 mil)   | 0.033             | 0.009 | 0.005      |
| 4.6 mm (180 mil)   | 0.033             | 0.027 | 0.007      |

## Mechanical

|                                  |  |
|----------------------------------|--|
| Probe Tip Material               | Polyphenylene sulfide (PPS).   |
| Probe Case Material              | AISI 304 stainless steel (SST).  |
| Probe Cable Specification        | 75 $\Omega$ triaxial, fluoroethylene propylene (FEP) insulated probe cable in the following total probe lengths: 1, 5 or 9 meters. |
| Extension Cable Material         | 75 $\Omega$ triaxial, fluoroethylene propylene (FEP) insulated.  |
| Proximator Sensor Material       | A380 aluminum  |
| System Length                    | 5 or 9 meters including extension cable  |
| Extension Cable Armor (optional) | Flexible AISI 302 SST with FEP outer jacket.   |
| Tensile Strength (maximum rated) | 330 N (75 pounds) probe case to probe lead. 270 N (60 pounds) at probe lead to extension cable connectors.                         |
| Connector Material               | Gold-plated brass  |

### Probe Case Torque

|                                 | Maximum Rated           | Recommended             |
|---------------------------------|-------------------------|-------------------------|
| 1/2-20 and 5/8-18 probe cases   | 45.2 N•m<br>(400 in•lb) | 15.2 N•m<br>(133 in•lb) |
| M14x1.5 and M16x1.5 probe cases | 63.3 N•m<br>(560 in•lb) | 21.1 N•m<br>(187 in•lb) |
| Reverse mount probes            | 22.6 N•m<br>(200 in•lb) | 7.5 N•m<br>(66 in•lb)   |

### Connector-to-connector torque

|   |                     |
|---|---------------------|
| Recommended torque                              | Finger tight        |
| Maximum torque                                  | 0.565 N•m (5 in•lb) |
| Minimum Bend Radius (with or without SST armor) | 25.4 mm (1.0 in)    |

### System Weight (typical)

#### Probe

70 g (2.5 oz) (minimum length case, 1m lead, no armor)

170 g (6.0 oz) (minimum length case, 1m lead, with armor)

For longer case lengths add 1.1 g/mm (1.0 oz/in).

For 5 m probe length add 180 g (6 oz) for non-armored probe or 560 g (20 oz) for armored probe.

For 9 m probe length add 360 g (12 oz) for non-armored probe or 1120 g (40 oz) for armored probe.

|                         |                     |
|-------------------------|---------------------|
| Extension Cable         | 45 g/m (0.5 oz/ft)  |
| Armored Extension Cable | 140 g/m (1.5 oz/ft) |
| Proximator Sensor       | 255 g (9 oz)        |

### Thread Engagement Limits

| Probe Case Thread | Maximum Length of Thread Engagement |
|-------------------|-------------------------------------|
| 1/2-20            | 0.750 in                            |
| 5/8-18            | 0.938 in                            |

| Probe Case Thread | Maximum Length of Thread Engagement |
|-------------------|-------------------------------------|
| <b>M14x1.5</b>    | 21 mm                               |
| <b>M16x1.5</b>    | 24 mm                               |



Maximum thread engagement lengths are per the industry standard of 1.5 times the nominal thread diameter. A fit class matching that of the external probe thread is assumed for all internal threads. Applications with thread engagement lengths exceeding the values in the table above may exhibit binding during installation. Contact your Bently Nevada representative if you require probe thread engagement lengths exceeding the values above. Bently Nevada does not replace proximity probes under warranty due to excessive thread engagement lengths.

## Environmental Limits

### Probe Temperature Range

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Operating and Storage Temperature | -52°C to +177°C (-62°F to +351°F) |
|-----------------------------------|-----------------------------------|



Exposing the probe to temperatures below -34°C (30°F) may cause premature failure of the pressure seal.

### Extension Cable Temperature Range

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Operating and Storage Temperature | -52°C to +177°C (-62°F to +351°F) |
|-----------------------------------|-----------------------------------|

### Proximitor Sensor Temperature Range

|                       |                                   |
|-----------------------|-----------------------------------|
| Operating Temperature | -52°C to +100°C (-62°F to +212°F) |
|-----------------------|-----------------------------------|

|                     |   |
|---------------------|---|
| Storage Temperature | -52°C to +105°C (-62°F to +221°F)   |
| Relative Humidity   | 100% condensing, non-submersible when connectors are protected. Tested to IEC 68-2-3 damp heat.   |
| Probe Pressure      | 3300 XL probes are designed to seal differential pressure between the probe tip and case. The probe sealing material consists of a Viton O-ring. Probes are not pressure tested prior to shipment. Contact our custom design department if you require a test of the pressure seal for your application |



It is the responsibility of the customer or user to ensure that all liquids and gases are contained and safely controlled should leakage occur from a proximity probe. In addition, solutions with high or low pH values may erode the tip assembly of the probe causing media leakage into surrounding areas. Bently Nevada not be held responsible for any damages resulting from leaking 3300 XL proximity probes. In addition, 3300 XL proximity probes does not be replaced under the service plan due to probe leakage.



## Compliance and Certifications

### FCC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

### EMC

European Community Directive:

EMC Directive 2014/30/EU

Standards

EN 61000-6-2; Immunity for Industrial Environments

EN 61000-6-4; Emissions for Industrial Environments

### RoHS

European Community Directive:

RoHS Directive 2011/65/EU

### Maritime

2019 Rules for Conditions of Classification,  
Part 1, 1-1-1/7.7, 1-1-A3, 1-1-A4

2019 Rules for Conditions of Classification,  
Part 1, Offshore Units and Structures  
1-1-4/9.7, 1-1-A2, 1-1-A3

### Functional Safety

SIL 2, HFT = 0

SIL 3, HFT = 1

## Hazardous Area Approvals



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

### cNRTLus

#### 3300 XL Proximito Sensor

|  |  |
|--|--|
| <b>ia</b><br><br>When installed with intrinsically safe zener barriers per drawing 141092 or when installed with galvanic isolators. | Class I, Zone 0: AEx/Ex ia IIC T4/T5 Gc;<br>Class I, Groups A, B, C, and D,<br>Class II, Groups E, F and G,<br>Class III;<br><br>T5 @ Ta= -55°C to + 40°C.<br>T4 @ Ta= -55°C to + 80°C.  |
| <b>nA, ec</b><br><br>When installed with non-incendive circuit connected per drawing 140979.   | Class I, Zone 2: AEx/Ex nA IIC T4/T5 Gc;<br>Class I, Division 2, Groups A, B, C, and D;<br>Class I, Zone 2: AEx/Ex ec IIC T4/T5 Gc;<br>Class I, Division 2, Groups A, B, C, and D;<br><br>T5 @ Ta= -55°C to + 40°C<br>T4 @ Ta= -55°C to + 80°C |



#### 3300 XL Probe

|  |  |
|--|--|
| <b>ia</b><br><br>When installed with intrinsically safe zener barriers per drawing 141092 or when installed with galvanic isolators. | Class I, Zone 0: AEx/Ex ia IIC T5...T1 Gc;<br>Class I, Groups A, B, C, and D,<br>Class II, Groups E, F, and G,<br>Class III;<br><br>(see Temperature Schedule table to follow) |
|--|--|

|  |  |
|--|--|
| <b>nA, ec</b><br>When installed with non-incendive circuit connected per drawing 140979. | Class I, Zone 2: AEx/Ex nA IIC T5...T1 Gc;<br>Class I, Division 2, Groups A, B, C, D;<br>Class I, Zone 2: AEx/Ex ec IIC T5...T1 Gc;<br>Class I, Division 2, Groups A, B, C, and D;<br>(see Temperature Schedule table to follow) |
|--|--|

## ATEX/IECEx



### 3300 XL Proximity Sensor

|              |  |           |             |            |            |            |             |           |            |             |            |
|--------------|--|-----------|-------------|------------|------------|------------|-------------|-----------|------------|-------------|------------|
| <b>ia</b>    |  <p>II 1 G<br/>Ex ia IIC T4/T5 Ga<br/>Ex ia IIIC T90C/T105C Dc<br/>For EPL Dc:<br/>T105C @ Ta = -55°C to 100°C<br/>T90C @ Ta = -55°C to +85°C</p> <table> <tr><td>Ui = -28V</td><td>Uo = -28V</td></tr> <tr><td>Ii = 140mA</td><td>Io = 140mA</td></tr> <tr><td>Pi = 0.91W</td><td>Po = 0.742W</td></tr> <tr><td>Ci = 47nF</td><td>Co = 1.5nF</td></tr> <tr><td>Li = 1460µH</td><td>Lo = 610µH</td></tr> </table> | Ui = -28V | Uo = -28V   | Ii = 140mA | Io = 140mA | Pi = 0.91W | Po = 0.742W | Ci = 47nF | Co = 1.5nF | Li = 1460µH | Lo = 610µH |
| Ui = -28V    | Uo = -28V  |           |             |            |            |            |             |           |            |             |            |
| Ii = 140mA   | Io = 140mA   |           |             |            |            |            |             |           |            |             |            |
| Pi = 0.91W   | Po = 0.742W  |           |             |            |            |            |             |           |            |             |            |
| Ci = 47nF    | Co = 1.5nF   |           |             |            |            |            |             |           |            |             |            |
| Li = 1460µH  | Lo = 610µH   |           |             |            |            |            |             |           |            |             |            |
| <b>nA,ec</b> |  <p>II 3 G<br/>Ex nA IIC T4/T5 Gc<br/>Ex ec IIC T4/T5 Gc</p> <table> <tr><td>Ui = -28V</td><td>Ii = 140 mA</td></tr> </table> <p>T5 @ Ta = -55°C to +40°C<br/>T4 @ Ta = -55°C to +80°C</p>  | Ui = -28V | Ii = 140 mA |            |            |            |             |           |            |             |            |
| Ui = -28V    | Ii = 140 mA  |           |             |            |            |            |             |           |            |             |            |

### 3300 XL Probe



Probe entity parameters are met when used with BN extension cables and connected to BN Prox.

|              |  |           |             |             |             |             |  |
|--------------|--|-----------|-------------|-------------|-------------|-------------|--|
| <b>ia</b>    |  <p>II 1 G<br/>Ex ia IIC T5...T1 Ga,<br/>(see Temperature Schedule table to follow)<br/><br/>Ex ia IIIC T90°C ... T280°C Dc<br/>For EPL Dc:</p> <table> <tr><td>Ui = -28V</td><td>Ci = 1.5 nF</td></tr> <tr><td>Ii = 140 mA</td><td>Li = 610 µH</td></tr> <tr><td>Pi = 0.91 W</td><td></td></tr> </table> | Ui = -28V | Ci = 1.5 nF | Ii = 140 mA | Li = 610 µH | Pi = 0.91 W |  |
| Ui = -28V    | Ci = 1.5 nF  |           |             |             |             |             |  |
| Ii = 140 mA  | Li = 610 µH  |           |             |             |             |             |  |
| Pi = 0.91 W  |  |           |             |             |             |             |  |
| <b>nA,ec</b> |  <p>II 3 G<br/>Ex nA IIC T5...T1 Gc,<br/>Ex ec IIC T5...T1 Gc,<br/>(see Temperature Schedule table to follow)</p> <table> <tr><td>Ui = -28V</td><td>Ii = 140 mA</td></tr> </table>  | Ui = -28V | Ii = 140 mA |             |             |             |  |
| Ui = -28V    | Ii = 140 mA  |           |             |             |             |             |  |

## Temperature Schedule

| Temperature Classification | Ambient Temperature (Probe Only) |
|----------------------------|----------------------------------|
| For EPL Ga and Gc          |                                  |
| T1                         | -55°C to +232°C                  |
| T2                         | -55°C to +177°C                  |
| T3                         | -55°C to +120°C                  |
| T4                         | -55°C to +80°C                   |
| T5                         | -55°C to +40°C                   |
| For EPL Dc                 |                                  |
| T280°C @ Ta                | -55°C to +232°C                  |
| T225°C @ Ta                | -55°C to +177°C                  |
| T170°C @ Ta                | -55°C to +120°C                  |
| T130°C @ Ta                | -55°C to +80°C                   |
| T105°C @ Ta                | -55°C to +100°C                  |
| T90°C @ Ta                 | -55°C to +40°C                   |



---

## Hazardous Area Conditions of Safe Use

### cNRTLus:

#### **ia**

Install per Bently Nevada drawing 141092.

#### **nA, ec**

Install per Bently Nevada drawing 140979.

### ATEX/IECEx:

#### **ia**

Install per Bently Nevada drawing 141092.

#### **nA, ec**

The Proximitator must be installed so as to provide the terminals with a degree of protection of at least IP54.

## Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

### 3300 XL 11 mm Proximity Probes

**330701** 3300 XL 11 mm Probe, 1/2-20 UNF thread, without armor

**330702** 3300 XL 11 mm Probe, 1/2-20 UNF thread, with armor

**330707** 3300 XL 11 mm Probe, 5/8-18 UNF thread, without armor

**330708** 3300 XL 11 mm Probe, 5/8-18 UNF thread, with armor

**Part Number-AA-BB-CC-DD-EE-**

#### A: Unthreaded Length Option



Unthreaded length must be at least 1.0 inch less than the case length.

Order in increments of 0.1 in  
Length configurations:

**Maximum unthreaded length:**  
8.9 in

**Minimum unthreaded length:**  
0.0 in

Example: **0 4** = 0.4 in

#### B: Overall Case Length Option

Order in increments of 0.1 in  
Threaded length configurations:

**Maximum case length:** 9.9 in

**Minimum case length:** 1.0 in

Example: **2 4** = 2.4 in

#### C: Total Length Option

**10** 1.0 meter (3.3 feet)

**50** 5.0 meters (16.4 feet)

**90** 9.0 meters (29.5 feet)



Five meter probes are designed for use with the five meter Proximitor Sensor only.

#### D: Connector and Cable-Type Option

**01** Miniature coaxial ClickLoc connector with connector protector, standard cable

**02** Miniature coaxial ClickLoc connector, standard cable

**11** Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

**12** Miniature coaxial ClickLoc connector, FluidLoc cable

#### E: Agency Approval Option

**00** Not required

**05** Multiple Approvals

### 3300 XL 11 mm Proximity Probes, Metric

**330703** 3300 XL 11 mm Probe, M14 x 1.5 thread, without armor


**330704** 3300 XL 11 mm Probe, M14 x 1.5 thread, with armor

**330709** 3300 XL 11 mm Probe, M16 x 1.5 thread, without armor

**330710** 3300 XL 11 mm Probe, M16 x 1.5 thread, with armor

**Part Number-AAA-BBB-CC-DD-EE**


### A: Unthreaded Length Option

|  |  |
|--|--|
|  |  Unthreaded length must be at least 26 mm less than the case length.                        |
|  | Order in increments of 2 mm.<br>Length configuration:<br><b>Maximum unthreaded length:</b> 224 mm<br><b>Minimum unthreaded length:</b> 0 mm<br>Example: <b>0 6 0</b> = 60 mm |

### B: Overall Case Length Option

|  |   |
|--|---|
|  | Order in increments of 2 mm.<br>Metric thread configurations:<br><b>Maximum length:</b> 250 mm<br><b>Minimum length:</b> 26 mm<br>Example: <b>0 6 0</b> = 60 mm |
|--|---|

### C: Total Length Option

|           |  |
|-----------|--|
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>50</b> | 5.0 meters (16.4 feet)   |
| <b>90</b> | 9.0 meters (29.5 feet)<br> Five meter probes are designed for use with the five meter Proximitor Sensor only. |

### D: Connector and Cable-Type Option

|           |   |
|-----------|---|
| <b>01</b> | Miniature coaxial ClickLoc connector with connector protector, standard cable |
| <b>02</b> | Miniature coaxial ClickLoc connector, standard cable                          |
| <b>11</b> | Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable |

**12**

Miniature coaxial ClickLoc connector, FluidLoc cable

### E: Agency Approval Option


|           |                    |
|-----------|--------------------|
| <b>00</b> | Not required       |
| <b>05</b> | Multiple Approvals |

## 3300 XL 11 mm Reverse Mount Probe

**330705-02-18- CC-DD-EE** 3/8-24 UNF threads

**330706-005-046- CC-DD-EE** M10 x 1 threads

### C: Total Length Option

|           |  |
|-----------|--|
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>50</b> | 5.0 meters (16.4 feet)   |
| <b>90</b> | 9.0 meters (29.5 feet)<br> Five meter probes are designed for use with the five meter Proximitor Sensor only. |

### D: Connector Option

|           |                                      |
|-----------|--------------------------------------|
| <b>02</b> | Miniature ClickLoc coaxial connector |
|-----------|--------------------------------------|

### E: Agency Approval Option

|           |                    |
|-----------|--------------------|
| <b>00</b> | Not required       |
| <b>05</b> | Multiple Approvals |

For a shorter delivery time, order commonly stocked probes. Currently, stocked probes consist of the following part numbers: 330701-00-10-10-02-00, 330701-00-20-10-02-00, 330703-000-050-10-02-00, 330705-02-18-10-02-00, 330706-005-046-10-02-00.

## 3300 XL 11 mm Proximitior Sensor

### 330780-AA-BB

#### A: Total Length and Mounting Option

|           |  |
|-----------|--|
| <b>50</b> | 5.0 meter (16.4 feet) system length, panel mount           |
| <b>51</b> | 5.0 meter (16.4 feet) system length, DIN mount             |
| <b>52</b> | 5.0 meter (16.4 feet) system length, no mounting hardware  |
| <b>90</b> | 9.0 meters (29.5 feet) system length, panel mount          |
| <b>91</b> | 9.0 meters (29.5 feet) system length, DIN mount            |
| <b>92</b> | 9.0 meters (29.5 feet) system length, no mounting hardware |

#### B: Agency Approval Option

|           |                    |
|-----------|--------------------|
| <b>00</b> | Not required       |
| <b>05</b> | Multiple approvals |



Country specific approvals may be available, consult your local Customer Care Representative for more information.

## 3300 XL 11 mm Extension Cable

### 330730-AAA-BB-CC

Make sure that the extension cable length and the probe length, when added together, **equal the Proximitior Sensor Total length.**

#### A: Cable Length Option

|            |                        |
|------------|------------------------|
| <b>040</b> | 4.0 meters (13.1 feet) |
| <b>080</b> | 8.0 meters (26.2 feet) |

#### B: Connector and Cable Option

|           |   |
|-----------|---|
| <b>00</b> | Standard cable                                  |
| <b>01</b> | Armored cable                                   |
| <b>02</b> | Standard cable with connector protector         |
| <b>03</b> | Armored cable with connector protector          |
| <b>10</b> | FluidLoc cable                                  |
| <b>11</b> | Armored FluidLoc cable                          |
| <b>12</b> | FluidLoc cable with connector protector         |
| <b>13</b> | Armored FluidLoc cable with connector protector |

#### C: Agency Approval Option

|           |                    |
|-----------|--------------------|
| <b>00</b> | Not required       |
| <b>05</b> | Multiple Approvals |

## Accessories

|           |  |
|-----------|--|
| 146255    | 3300XL 11 mm User Guide  |
| 144979    | Performance Specification  |
| 02120015  | Bulk field wire. 1.0 mm <sup>2</sup> (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet. |
| 02173009  | Bulk field wire. 1.0 mm <sup>2</sup> (18 AWG), 3 conductor, twisted, shielded cable. Specify length in feet.                 |
| 138492-01 | Replacement panel-mount mounting pad   |
| 138493-01 | Replacement DIN-mount mounting pad   |
| 01609137  | BNC (F) to banana plugs  |
| 01609138  | Proximitior Connector Test Pin wiring (two test pins to a BNC (F) connector)   |

|           |  |           |   |
|-----------|--|-----------|---|
| 40971-04  | 50 $\Omega$ cable with two BNC (M) connectors. Use this cable in combination with adapter 01609137 and adapter 01609138 when checking performance of the transducer system from the Proximitor Sensor test pin holes.  | 03839420  | Female Connector Protector. Placed on the probe lead to connect to the male connector protector on the extension cable and provide environmental protection of connectors. Also placed on the extension cable to slide over the Proximitor Sensor connection and protect it from the environment. |
| 04310310  | 3300XL Proximitor Sensor Panel-mount Screws. Package includes four 6-32 UNC thread forming mounting screws (Supplied standard with 3300 XL Proximitor Housings [3300 XL option]).  | 330153-01 | 3300 XL Connector Kit. Used on 3300 XL probes and extension cables. Contains one set of male and female ClickLoc connectors, sleeves and one strip of silicone tape.  |
| 03200006  | Silicone Self-fusing tape. A 9.1 meter (10 yard) roll of silicone tape to protect connectors. It is easy to install and provides excellent electrical isolation and protection from the environment. It is not recommended for use inside the casing of the machine. | 163356    | Connector Crimp Tool Kit. Includes one set of 75 $\Omega$ 3300 XL ClickLoc inserts and connector installation instructions. Supplied with carrying case.  |
| 40113-02  | Connector Protector Kit. Connector Protector Kit for 3300 XL probes and extension cables, including connector protectors and installation tools.   |           |   |
| 136536-01 | Connector Protector Adapter.<br><br>Makes our previous 3300 connector protector kits compatible with 3300 XL probes and extension cable connectors.  |           |   |
| 40180-02  | Connector Protectors. Package contains 10 pairs of connector protectors.   |           |   |
| 03839410  | Male Connector Protector. Placed on the extension cable to connect to the female connector protector on the probe and provide environmental protection of connectors.  |           |   |

# Graphs and Figures




Figure 1: Typical 3300 XL 11 mm 5 m System Over Ambient Testing Range






Figure 2: Typical 3300 XL 11 mm 9 m System Over Ambient Testing Range







**Figure 3: Typical 3300 XL 11 mm Probe + 1 m Cable @ Low Temperature**  
(Proximitior Sensor + 4m of Extension Cable @ 25 °C)



**Figure 4: Typical 3300 XL 11 mm Probe + 1 m Cable @ High Temperature**  
(Proximitor Sensor + 4m of Extension Cable @ 25 °C)




**Figure 5: Typical 3300 XL 11 mm 5 m Proximitor Sensor with 4 m of Extension Cable @ Cold Temperature**  
(Probe is at 25°C)




**Figure 6: Typical 3300 XL 11 mm 5 m Proximity Sensor with 4 m Extension Cable @ High Temperature**


(Probe is at 25°C)




**Figure 7: Typical 3300 XL 11 mm 9 m Proximator Sensor with 8 m of Extension Cable @ Low Temperature**  
(Probe is at 25°C)



**Figure 8: Typical 3300 XL 11 mm 9 m Proximitior with 8 m of Extension Cable @ High Temperature**  
(Probe is at 25°C.)




**Figure 9: Frequency Response, magnitude of typical 3300 XL 11 mm System**  
with various lengths of field wiring, no barriers




**Figure 10: Frequency Response, phase change of typical 3300 XL 11 mm System**  
with various lengths of field wiring, no barriers






**Figure 11: 3300 XL 11 mm Proximity probes, Standard Mount**

- 330701, ½-20 UNF-2A, without armor
- 330702, ½-20 UNF-2A, with armor
- 330703, M14X1.5 thread, without armor
- 330704, M14X1.5 thread, with armor
- 330707, 5/8-18 UNF-2A, without armor
- 330708, 5/8-18 UNF-2A, with armor
- 330709, M16X1.5 thread, without armor
- 330710, M16X1.5 thread, with armor




Note: Connector Protector only installed on female end when optioned. Both ends available as accessories.

**Figure 12: Installed Connector Protectors**




**Figure 13: 3300 XL 11 mm Proximity Probes, Reverse Mount**


330705, 3/8-24 UNF-2A threads  
330706, M10X1 threads



**Figure 14: 330730, 3300 XL 11 mm Extension Cable**



**Figure 15: Panel Mount 3300 XL 11 mm Proximity Transducer**



**Figure 16: DIN Mount 3300 XL 11 mm Proximity Sensor**

Notes:

1. All dimensions on figures are in millimeters (inches) unless otherwise noted.
2. Standard mount  $\frac{1}{2}$ -20 UNF thread probes are supplied with  $\frac{3}{4}$  inch lock nut and  $\frac{7}{16}$  wrench flats.
3. Standard mount M14x1.5 thread probes are supplied with 22 mm lock nut and 12 mm wrench flats.
4. Standard mount  $\frac{5}{8}$ -18 UNF thread probes are supplied with  $\frac{15}{16}$  inch lock nut and  $\frac{9}{16}$  wrench flats.
5. Standard mount M16x1.5 thread probes are supplied with 24 mm lock nut and 14 mm wrench flats.
6. Reverse mount probes are not available with armor, FluidLoc cable or connector protector options.
7. Letters inside quotation marks on figures refer to probe ordering options.
8. Stainless steel armor is supplied with FEP outer jacket.
9. FEP jacket is standard on all non-armored probes.
10. Probes ordered with 5 or 9 meter integral cables have a length tolerance of +20%, -0%.

Copyright 2024 Baker Hughes Company. All rights reserved.



Bently Nevada, Keyphasor, M2, Proximitor and Orbit Logo are registered trademarks of Bently Nevada, a Baker Hughes business, in the United States and other countries. The Baker Hughes logo is a trademark of Baker Hughes Company. All other product and company names are trademarks of their respective holders. Use of the trademarks does not imply any affiliation with or endorsement by the respective holders.

Baker Hughes provides this information on an "as is" basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

The information contained in this document is the property of Baker Hughes and its affiliates; and is subject to change without prior notice. It is being supplied as a service to our customers and may not be altered or its content repackaged without the express written consent of Baker Hughes. This product or associated products may be covered by one or more patents. See [Bently.com/legal](https://www.bently.com/legal).

1631 Bently Parkway South, Minden, Nevada USA 89423  
Phone: 1.775.782.3611 (US) or [Bently.com/support](https://www.bently.com/support)  
[Bently.com](https://www.bently.com)